



Push Button

- Mounting diameter (mm) : 12,16,19,22,25,28,30
- Shape of head : Flat/ Ball/ High
- Contact type : 1NO, 1NO+NC, 2NO+ 2NC
- Operation type : Momentary (M) + Latched (L)
- Shell material : Brass/ Stainless Steel
- Type : Illuminated (AE)/ Non-Illuminated (A)
- Luminous color : R G Y O B W
- Lamp Type : Ring/ Dot (D)/ Power Symbol (P)
- Terminal : Pin/ Screw
- IP Degree : IP 67(water proof grade)
- Related Voltage : DC-12V, 24V, 36V & 220VAC



For genuineness please check mark **ARIHANT**.


Emergency Switch

- Mounting diameter (mm) : 19,22
- Front shape : Ball Head Mushroom
- Shell material : SS
- Contact: 1NO+ 1NC, 2NO+2NC
- Operation type : Push Pull/ Turn To Release
- Color : Red
- IP Degree : IP 67



Connector

- Type : Plug-16
Plug-19
Plug-22
Plug- 25
- Cable Length :- ½ Meter Standard



A-82, Okhla Industrial Area, Phase 2, New Delhi - 110020(INDIA)

E mail : info@arihantelectricals.com | +91- 11- 47637300

Group Company - Arihant Electricals (www.arihantelectricals.com)

Arihant Elsys Pvt Ltd (www.arisysel.com)

Delhi | Pune | Mumbai | Rourkela | Ahmedabad | Chandigarh | Bengaluru | Chennai | Hyderabad | Lucknow | Bhopal | Bhubaneswar
Kolkata | Kathmandu



Selector Switch

- Measuring Diameter : 19,22
- Contact : 1NO+ NC, 2NO+ 2NC
- Front Shape : Selector/ Flat Round
- Operation Type : 2 Position
3 Position
- Shell Material : SS

• Color : R Y G B W

- Rated Voltage : DC-24V & AC -220V
- IP Degree : 67



Signal Lamp

- Mounting Diameter (mm) :
8,12,16,19,22,25,30

• Type : LED

• Color : R Y G B W

- Rated Voltage : AC/DC-6V.....220V
- Shell Material : Copper Plating / SS
- Ip Degree : 68



Ordering Code

Product	Meeting Dia (mm)	Rated Voltage	Color	Operation Type	Head Type	Lamp	Contacts		
A - Non Illuminated	8	DC- 12V 24V 36V AC-220V	W	M-Momentary L - Latched	F- Flat B- Ball H- Head	- : Ring D : Dot P : Power Symbol	- : 1NO+ 1NC 1: NO 2 : 2NO + 2NC		
AE- Illuminated	12		R						
E- Emergency Button	16							Y	
S- Selector Switch	19								G
SL -Signal Lamp	22								
	25								
	30								

Ordering Example AE 16/24/R-L-F/D/2